

-SINGLE PHASE TEFC MOTOR (≤ 10HP) -50 Hz INVERTER DUTY MOTOR

-UP TO 250HP 3 PHASE MOTOR

-SANITARY MOTOR

-EXPLOSION PROOF MOTOR

-ALTERNATE IMPELLER SIZES AND TYPES

-SANITARY FINISHES

DIM H

DIML

9.8"

22.4"

11.2"

23.2"

12.7"

28.8"


14.5"

31.7"



ITEM	DESCRIPTION
1	MOTOR - 230/460/60, 3 PHASE, TEFC STANDARD, INVERTER DUTY (10:1),
	PAINTED FINISH
- つ	GEARBOX - HELICAL/BEVEL DRIVE, OUTPUT SPEED PER ORDER, CAST
	IRON, PAINTED FINISH
3	MOUNT - OPEN TANK MOUNT - SEE TABLE FOR DETAILS
1	SHAFT - LENGTH AND DIAMETER PER ORDER 316SS TYP

IMPELLER - SIZE, STYLE, & QTY PER ORDER, 316SS TYP.



BOLTED PF3
HYDROFOIL

BOLTED PBT (PITCH
BLADE TURBINE)

RADIAL

RUSHTON

PV3 PROP

17.8"

36.8"

20.0"

45.3"

23.1"

52.6"

28.0"

54.7"

32.1"

58.8"

35.8"

60.6"

DRAWN SB 5/27/22
CHECKED MB 6/24/22
PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FUSION FLUID EQUIPMENT LLC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FUSION FLUID EQUIPMENT LLC IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED

DIMENSIONS ARE IN INCHES.

NO TOLERANCES IMPLIED

DO NOT SCALE DRAWING

FUSION FLUID CQUIPMENT

TLE: FUSION FLOW FR3-M TOP ENTRY CIRCULAR MOUNT MIXER HELICAL/BEVEL DRIVE OPEN TANK