



MOST COMMON AVAILABLE OPTIONS:

- SINGLE PHASE TEFC MOTOR (≤ 10 HP)
- 60 Hz INVERTER DUTY MOTOR
- EXPLOSION PROOF MOTOR
- ALTERNATE IMPELLER SIZES AND TYPES
- ALTERNATE WETTED PARTS MATERIAL
- SANITARY FINISHES
- STAINLESS STEEL SANITARY MOTOR AND DRIVE



ITEM NO.	DESCRIPTION
1	MOTOR - 230/460V, 60 Hz, 3 PHASE, STAINLESS STEEL
2	GEARBOX - WORM DRIVE, OUTPUT SPEED PER ORDER, STAINLESS STEEL
3	MOUNT - ANGLE RISER, STAINLESS STEEL
4	SHAFT - SIZE PER ORDER, STAINLESS STEEL
5	IMPELLER - MATERIAL, STYLE, SIZE & QTY PER ORDER



MODEL	FWS-1.54	FWS-1.75	FWS-1.97	FWS-2.38	FWS-3.00
DIM A	9.63	9.63	9.63	CONSULT FACTORY FOR DIMENSIONS	
DIM B	6.5	6.5	6.5		
DIM H	9.72	9.38	10.29		
DIM L	20.67	20.91	22.09		

DIMENSIONS NOTED ARE APPROXIMATE AND ARE BASED ON STANDARD MIXER SELECTION. MOTOR SELECTION WILL AFFECT OVERALL LENGTH. PLEASE CONTACT FUSION FOR FURTHER DETAILS.

TYPICAL IMPELLER OPTIONS

BIOPROP	PF3 HYDROFOIL	PBT (PITCH BLADE TURBINE)	RETREAT	RUSHTON	PV3 PROP



UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
NO TOLERANCE IS IMPLIED.
DO NOT SCALE DRAWING

DRAWN	NAME	DATE
CHECKED	DH	02/05/26
	JM	07/08/26
PROPRIETARY AND CONFIDENTIAL		
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FUSION FLUID EQUIPMENT LLC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FUSION FLUID EQUIPMENT LLC IS PROHIBITED.		
WHILE FUSION FLUID EQUIPMENT LLC STRIVES TO MAINTAIN THE INTEGRITY OF A DESIGN AS APPROVED, FUSION FLUID EQUIPMENT LLC RETAINS THE RIGHT TO MAKE MODIFICATIONS DURING THE MANUFACTURING PROCESS TO IMPROVE FIT, FORM, AND FUNCTION OF THE DESIGN WITHOUT CUSTOMER NOTIFICATION OR CONSENT.		



TITLE: FUSION FLOW FWS TOP ENTRY ANGLE MOUNT MIXER STAINLESS WORM DRIVE OPEN TANK		
SIZE	DWG. NO.	REV
A	SALES-FWS-###A	B
SCALE: 1:16	WEIGHT:	SHEET 1 OF 1